

FLYERS ATF D/M III

State-of-the-art additive system provides ultimate protection and peak performance.

PRODUCT DESCRIPTION

Recommended for applications that call for the former DEXRON®-III H, MERCON®, and Allison C-4 fluids.

FEATURES

Flyers ATF is a premium transmission fluid designed and recommended for use in automatic transmissions previously serviceable by GM DEXRON®-III (H) and Ford MERCON® brands. It may also be used in equipment requiring a "Type A" ATF Fluid, Allison C-4, Caterpillar TO-2, and Ford specifications M2C138-CJ and M2C166-H.

Flyers ATF's state-of-the-art additive system provides ultimate protection and peak performance in passenger cars, SUVs and light trucks. FLYERS ATF is not recommended for use in transmissions requiring GM DEXRON®-VI, Ford MERCON®-V and MERCON® SP fluids.

Flyers ATF also makes an excellent hydraulic fluid in mobile or industrial applications where low temperature fluidity or leak detection is an important consideration.

FLYERS ATF D/M III TEST DATA

Density, g/cm ³	0.860
Flash Point, COC C°(F°)	212 (413)
Viscosity, cP @ -20 C°	1300
Viscosity, cP @ -30 C°	4200
Viscosity, cP @ -40 C°	17000
Viscosity, cP @ 40 C°	35.4
Viscosity, cP @ 100 C°	7.2
Viscosity Index	172
Pour Point, C°(F°)	-52 (-61)
Color	Red
Foam Test, ASTM D892	Pass

CUSTOMER BENEFITS

Exceptional stability provided by premium base oils and extra oxidation inhibitors.

Quiet performance — especially effective in minimizing transmission "chatter." Helps ensure smooth, quiet action at all speeds.

Fast circulation during cold weather and excellent film strength when hot.

Protection against the formation of lacquers, sludge, or other harmful deposits.

APPLICATIONS

Flyers ATF is formulated to provide:

- Superior wear protection
- Excellent frictional properties for smooth shifting
- Excellent anti-shudder performance
- Good seal compatibility
- Protection against varnish and sludge formation
- Superior thermal stability and oxidation resistance
- Outstanding low-temperature performance



